



**POWERFUL,
LIGHT, EASY.**

FP503 NEW PNEUMATIC HAND SHEAR

FP503. The smallest and powerful pneumatic scissor as ever.



1946




WHAT'S NEW:

Central back-located air exhaust
Strengthened structure for hard materials
New integrated sharpening device
High manageability in 800 g

PETRONI SRL
Via A.Bucchi, 1/B
06012 Città di Castello (PG)
+39 075/852.07.87

www.petronisrl.it

NEW PNEUMATIC HAND SHEAR FP503



minimum recommended

TECHNICAL DETAILS:

Muffled turbine motor with central back-located air exhaust
6 bar nominal* (± 1 bar) lubricated air supply

Air consumption: 9 std liters/sec*

Power: 350 W at nominal air supply conditions

Blade: 50 mm with hard metal counterblade

Blade descr.: 503EHSS, 50 mm dia., 6-edge, HSS steel

Blade speed: 1900 r.p.m.*

Cutting ability: up to 9 mm

Sound pressure: 72 dBe (EN ISO 15744)*

Vibration Level: 1,36 m/sec² (ISO 8662)*


Net weight: 800 g

Total weight (with packing): 1630 g

Temperature range: 0 – 55 C

Umidity range: 10 – 95% without condensate

**The reported data are collected at a pressure of 6 bar (ISO 2787: 1984), recommended operating pressure.*



Rasor recommend to use only dry air lubricated with special Rasor VG 10 pneumatic oil



BLADES AVAILABLE:

503EEXT, 50 mm 6-edges, EXTRA steel

503EHSS, 50 mm 6-edges, HSS steel

503CHSS, 50 mm circular, HSS steel

503DHSS, 50 mm 10-edges, HSS steel

503EHSSTF, 50 mm 6-edges, HSS steel

Teflon[®]coated

503DHSSTF, 50 mm 10-edges, HSS steel

Teflon[®]coated