



POWERFUL,
LIGHT, EASY.

FP503MT NEW PNEUMATIC HAND SHEAR

FP503MT. - The smallest and powerful pneumatic shear for edge trimming.



1946



WHAT'S NEW:

Central back-located air exhaust
Integrated slim foot for edge trimming
Integrated welded counterblade
High manageability in 780 g

PETRONI SRL
Via A.Bucchi, 1/B
06012 Città di Castello (PG)
+39 075/852.07.87

www.petronisrl.it

TECHNICAL DETAILS:

Muffled turbine motor with central back-located air exhaust 6 bar nominal* (± 1 bar) lubricated air supply

Air consumption: 9 std liters/sec*

Power: 350 W at nominal air supply conditions

Blade: 50 mm with hard metal counterblade

Blade descr.: 50SGHSS, 50 mm dia., 7-edge, HSS steel

Blade speed: 1900 r.p.m.*

Cutting ability: up to 8 mm

Sound pressure: 72 dBe (EN ISO 15744)*

Vibration Level: 1,36 m/sec² (ISO 8662)*

Net weight: 780 g

Total weight (with packing): 1600 g

Temperature range: 0 – 55 C

Umidity range: 10 – 95% without condensate

**The reported data are collected at a pressure of 6 bar (ISO 2787: 1984), recommended operating pressure.*

NEW PNEUMATIC HAND SHEAR FP503MT



Rasor recommend to use only dry air lubricated with special Rasor VG 10 pneumatic oil



minimum recommended



BLADES AVAILABLE:

50SEXTG, 50 mm, 7-edges EXTRA GERMAN steel | **50SGHSS**, 50 mm, 7-edges HSS GERMANY steel | **50CHSS**, 50 mm, circular HSS steel | **50CK**, 50 mm, circular K190 steel | **50SGHSSTF**, 50 mm, 7-edges HSS steel Teflon® coated.