

NEW
5 WINGS ROTOR
FOR MORE POWER
NEW GEARS
1300 RPM



FP702

NEW PNEUMATIC HAND SHEAR

New FP702. The new cutting solution. Suitable for leather.



1946



1946

WHAT'S NEW:

New 5 wings turbine

New gears 1300 rpm

New housing coating for heat reducing

High manageability in 920 g

PETRONI SRL

Via A.Bucchi, 1/B

06012 Città di Castello (PG)

+39 075/852.07.87

www.petronisrl.it

NEW PNEUMATIC HAND SHEAR

CE FP702



TECHNICAL DETAILS:

Muffled turbine motor with central back-located air exhaust

6 bar nominal* (± 1 bar) lubricated air supply

Air consumption: 9 std liters/sec*

Power: 380 W at nominal air supply conditions

Blade: 70 mm with hard metal counterblade

Blade descr.: 70EHSS, 70 mm dia., 6-edge, HSS steel

Blade speed: 1300 r.p.m.*

Cutting ability: up to 20 mm

Sound pressure: 72 dBe (EN ISO 15744)*

Vibration Level: 1,36 m/sec² (ISO 8662)*

Net weight: 920 g

Total weight (with packing): 1750 g


Temperature range: 0 – 55 C

Umidity range: 10 – 95% without condensate

**The reported data are collected at a pressure of 6 bar (ISO 2787: 1984), recommended operating pressure.*



Minimum recommended



Rasor recommend to use only dry air lubricated with special Rasor VG 10 pneumatic oil



BLADES AVAILABLE:

70SHSS, 70 mm 4-edges, HSS steel | **70EHSS**, 70 mm 6-edges, HSS steel | **70CHSS**, 70 mm circular, HSS steel | **70DHSS**, 70 mm 10-edges, HSS steel | **70SHSSTF**, 70 mm 4-edges, HSS steel Teflon[®] coated | **70EHSSTF**, 70 mm 6-edges, HSS steel Teflon[®] coated | **70EMD**, 70 mm 6-edges, Carbide (Widia[®]) | **70DHSSTN**, 70 mm 10-edges, HSS steel Titanium coated | **70DHSSTF**, 70 mm 10-edges, HSS steel Teflon[®] coated