

1946

SW100 ELECTRIC BENCH CUTTER

SW100. Flexibility and reliability since 50 years.



WHAT'S NEW:

Low-friction Teflon® coated plate New double safety starting system New main power switch with Led

TECHNICAL DETAILS:

Blade diameter: 100 mm (4"), with hard

metal counterblade

Blade equipped: 10EHSS, 6-edges, HSS steel

Blade speed: 850 r.p.m.

Cutting ability: up to 35 mm (1.4") Power: single phase - 90 W

Max. absorption: 2 A, with protection fuse **Net weight:** 2950 g (with power supply cord) Total weight (with packing box): 4550 q **Electric cable length:** 1.5 mt (with no plug) Minimum brightness for working

operations: LUX 200

Vibrations at start up: < 2.5 m/sec 2

Temperature range: $0 - 55 \, \text{C}$ **Umidity range:** 10 - 95% without

condensate





ELECTRIC BENCH CUTTER







BLADES AVAILABLE:

10EHSS, 100 mm 6-edges, HSS steel | **10SEXTG**, 100 mm 4-edges, EXTRA steel | **10CSW**, 100 mm circular, HSS steel | 10EHSSTF, 100 mm 6-edges, HSS steel Teflon® coated | 10EMD, 100 mm 6-edges, Carbide (Widia®)



PETRONI SRL Via A.Bucchi, 1/B 06012 Città di Castello (PG)

www.petronisrl.it

+39 075/852.07.87